# Proxy Settings guide

This comprehensive article is designed to guide every user within the University of Moratuwa (UoM) through the process of independently enabling and configuring proxy settings on internal computers. Discover step-by-step instructions that empower users to seamlessly manage their proxy configurations, ensuring a smooth and secure online experience across the university's network. Take control of your online privacy and connectivity with this user-friendly tutorial, tailored to meet the specific needs of UoM's diverse user base.

- Proxy Settings for UoM internal devices.
    - Proxy setting for UoM internal devices step by step guide.

Proxy Settings for UoM internal devices.

Proxy setting for UoM internal devices step by step guide.

- **Click on the start menu > Search for proxy > Click on proxy settings.**

-

- **Make sure that "Automatically detect settings" is turned off. Then click on "Set up" button which is under "Use a proxy server" setting.**

-

  Network & internet › **Proxy**

  Use a proxy server for Ethernet or Wi-Fi connections. These settings don't apply to VPN connections.

  Automatic proxy setup

  Make sure this

  Automatically detect settings   Off ⬤

  Use setup script
  Off   Set up

  Manual proxy setup

  Use a proxy server
  Off   Click on Set up ⟹   Set up

- **Turn on "Use a proxy server, and enter (copy and paste) the below values to the respective places. Check "Don't use the proxy server for local (intranet) addresses." Finally, click save.**

  - **Proxy IP address:**

  - cache. uom. lk

  - **Port:**

  - 3128

  - **Use the proxy server except for addresses that start with the following entries. Use semicolons (;) to separate entries.**

  - localhost; *. local; <local>; *. uom. lk; *. codl. lk; *. mrt. ac. lk

Edit proxy server

Use a proxy server

On ⟵ Turn this on

Copy and paste
the values from
the description

Proxy IP address

cache.uom.lk

Port

3128

Use the proxy server except for addresses that start with the following entries.
Use semicolons (;) to separate entries.

localhost;*.local;<local>;*.uom.lk;
.codl.lk;.mrt.ac.lk

☑ Don't use the proxy server for local (intranet) addresses

⇧ Check the check box

| Save | Cancel |